

said first sheet in a case where said first sheet is transported along said deflecting guide part;

a second transporting guide, provided along said first transporting guide, being formed

10 so as to transport a second sheet;

a second apparatus, provided at said second transporting guide, and performing processing for said second sheet in a case where said second sheet is transported along said second transporting guide;

15 wherein a portion of said second transporting guide which faces to said deflecting guide part is movable, so that said first apparatus can be exposed.

REMARKS

Claim 38 has been amended to provide a more concise presentation of the invention.

New matter has not been added.

Favorable action on the merits of this application is respectfully requested.

Respectfully submitted
for Applicant,

By: 

John James McGlew
Registration No. 31,903
McGLEW AND TUTTLE, P.C.

JJM:ed
56356RCE3.1

DATED: June 20, 2003
SCARBOROUGH STATION
SCARBOROUGH, NEW YORK 10510-0827
(914) 941-5600

SHOULD ANY OTHER FEE BE REQUIRED, THE PATENT AND TRADEMARK OFFICE IS HEREBY REQUESTED TO CHARGE SUCH FEE TO OUR DEPOSIT ACCOUNT 13-0410.

I HEREBY CERTIFY THAT THIS CORRESPONDENCE IS BEING DEPOSITED WITH THE UNITED STATES POSTAL SERVICE AS EXPRESS MAIL IN AN ENVELOPE ADDRESSED TO: COMMISSIONER FOR PATENTS, P.O. BOX 1450, ALEXANDRIA, VA. 22313-1450, NO.: EV 323 629 089 US

McGLEW AND TUTTLE, P.C.
SCARBOROUGH STATION, SCARBOROUGH, NY 10510-0827

BY:  DATE: June 20, 2003

Marked-up Version of Claim 38 Showing Changes Made

38. (Amended) A multiple function apparatus, comprising:

a first transporting guide including a straight guide part and a deflecting guide part, said straight guide part being formed so as to transport a first sheet straight and is open at one end, and said deflecting guide part being connected to said straight guide part at a side opposite said one end so as to transport a first sheet in a direction different from a direction of transport effected by said straight guide part;

a first apparatus provided at said deflecting guide part, and performing processing for said first sheet in a case where said first sheet is transported along said deflecting guide part;

a second transporting guide, provided along said first transporting guide, being formed so as to transport a second sheet;

a second apparatus, provided at said second transporting guide, and performing processing for said second sheet in a case where said second sheet is transported along said second transporting guide;

wherein a portion of said second transporting guide which faces to said deflecting guide part is movable, so that said first apparatus can be exposed

~~wherein said first apparatus is disposed in a space between said deflecting guide part and said second transporting guide, and at least at one portion of a section at which said first apparatus is disposed, said section included in said deflection guide part, a distance between said one portion and said second transporting guide in a direction vertical to transporting direction of said deflecting guide portion is longer than a distance between said straight guide part and second transporting guide.~~